



Pecu Tile Adhesive

Description

A product based on cement, specific aggregates, and additive materials and combined resins that make high adhesion and efficacy. This product, having high efficiency, is appropriate for tiling the swimming pools and the beds that are in touch with water and tiling on plaster panels.

Advantages and Applications

- Appropriate for floor tiling, inside and outside the building and exterior walls.
- Appropriate for gluing ceramic tiles whose power of absorption is average and high.
- As this adhesive can preserve the moisture, there is no need to moisturize the bed or tiles.
- Without slippage and having high primary adhesive power
- Having the capability of setting the tiles of without caulk.
- Resistant against moisture and appropriate for the use in swimming pools.

Dosage

The rougher a surface is, the more adhesive is needed. However, 4 kilograms of this powder could cover 1 square meter.

How to use

Gently add 4 kilograms of this powder to 1 liter of water and mix it with hand or mechanical mixer so that it will be quite homogenous. Wait for 5 minutes and then mix it again. Rub the paste, with a maximum 2mm thickness, on the given surface by a trowel. Disperse the paste with a toothed trowel to regulate its thickness. Put the tile on the paste, press it and turn a little to make sure that the paste is completely attached to the tile.

Notice: To have a better performance, put the tile on the paste immediately after it is rubbed on the surface.





Specifications:

Appearance: white or gray powder

Bulk density: $1.7 \pm 0.2 \text{g/cm}^2$

Paste density: $1.6 \pm 0.2 \text{g/cm}^2$

Shelf time: approximately 2 hours (concerning weather conditions)

Approximate efficiency: 4kg/m^2

Packaging and maintenance conditions

Keep in 4-ply 25-kg packages with plastic cover in roofed places out of sunlight.

